

TOWN OF CHILI



BUILDING DEPARTMENT 3333 CHILI AVENUE, ROCHESTER, NY 14624 PH: (585) 889-6143 Email: building@townofchili.org

POOL/HOT TUB PERMIT APPLICATION

Location of Work Address City, State, Zip Property Owner Information Name Address City, State, Zim	Zoning Classification FPO FW Tax I.D. # FPO FW PERMIT TYPE CHECK ALL THAT APPLY BELOW: Inground Pool Size: Height:
City, State, Zip Phone Email	□ Hot Tub (мизт наче LOCKING COVER) □ Pre-Existing Structure/ Work (no permit on record) Description of work
New York State Requires that the Town has on file a current certificate of insurance for both general liability and worker's compensation for the entity performing work prior to issuance of any building permit Contractor Information Company Name Contact Name	
Address City, State, Zip Phone Email	Estimated cost/value of project \$ POOL/HOT TUB PERMITS ARE VALID FOR 90 DAYS
The following must be submitted for a completed application to be reviewed (additional information may be required) A survey map that shows the property in detail, including:	
Owner/Reps. Signature	Date
<u>Inspections:</u> Inspections are required during the building process.*24 HOUR N When checked, the following inspections will be required for this project:	OTICE IS REQUIRED WHEN SCHEDULING INSPECTIONS*

□ Site Inspection □ Rough Electrical Inspection □ Final Electrical Inspection □ Final Inspection (REQUIRED TO CLOSE PERMIT) *CERTIFICATE OF COMPLIANCE MUST BE ISSUED PRIOR TO POOL/ HOT TUB BEING USED*

Electrical Inspections: An inspection is required for both rough and final electrical work. Proof of a final electrical inspection is required prior to a final building inspection. Electrical inspections are scheduled by contacting any of the two agencies listed below:

> Middle Dept. Insp. Agency 460 State street Rochester, NY 14608 (585) 454-5191

New York Elec. Insp. Agency 2767 Dewey Avenue Rochester, NY 14616 (585) 436-4460

- Setback requirements: A pool may not be located in the front yard. However, any swimming pool erected on a corner lot shall not be nearer than the secondary frontage setback of the existing dwelling. It must be at least 10 feet from side and rear lot lines. Also, above-ground pools may not be closer than 10 feet from any portion of the main dwelling; in-ground pools may not be closer than 15 feet (open porches and decks excluded
- Overhead electric wires: The National Electrical Code requires that all pools must be located at least 10 feet from overhead electrical wires.
- **Distance from well or septic system:** A pool must be located at least 10 feet from any active well or septic tank, leach lines, etc.
- Water supply: No fixed or direct connection may exist between the pool and the potable water supply.
- **Drainage:** No drainage of pool water is permitted to a sanitary sewer or onto adjacent property.

• Barrier requirements:

- With the exception of spas or hot tubs with an approved safety cover, and pools at least 48 inches high measured from the surrounding grade, all swimming pools must be enclosed.
- The barrier or enclosure must be at least 48 inches above the surrounding grade, measured on the side facing away from the pool. The maximum vertical clearance to grade is 2 inches.
- Any openings in the barrier cannot allow passage of a 4-inch-diameter sphere.
- Maximum mesh size for chain-link fences shall be a 2.25-inch square.
- The wall of a dwelling is permitted to serve as part of the enclosure, provided that the pool is equipped with an approved safety cover, or all doors with direct access to the pool are equipped with an alarm that sounds when the door is opened, or other adequate means of protection are provided.
- Access gates: Any gates to be provided for an enclosure must be self-closing and self-latching and shall be securely locked when the pool is not in use. Pool gates must be out swinging from the deck.
- **Decks:** Pools with an attached deck must also conform to the applicable requirements for decks. For more information, contact the Building Department.

• Required safety equipment:

- A rescue pole whose length is at least ½ of the pool's width, stored within 15 feet of the pool; a ladder no more than 2 feet from the bottom of the pool for a quick exit.
- An audible pool alarm is required (at the pool) which is capable of detecting entry into the water at any point on the surface of the swimming pool, and which also sounds an alarm in the house.

For Official Use	Permit #
Reviewed by	_ Date
Code Enforcement Officer	
Called for pickup	
Date Notes	
□ Homeowner □ Contractor □ Plumber	
Paid	
Date Receipt #	